International Journal for Multidisciplinary Research (IJFMR)

E-ISSN: 2582-2160 ● Website: www.ijfmr.com ● Email: editor@ijfmr.com

Scalable Kubernetes-Based Data Engineering Pipelines with Airflow and Kubeflow for Industrial IoT Analytics

Urvangkumar Kothari

Data Engineer
Las Vegas, NV, USA
Email: urvangkothari87@gmail.com

Abstract:
Industrial Internet of Things (IIoT) is producing huge amounts of sensor and machine data, which needs robust scalable, and efficient data playbooks. After reading the present paper, the reader should have an understanding of how to build and implement a modular and cloud-native data engineering pipeline architecture, based on Kubernetes but which leverages Apache Airflow as a workflow orchestration tool, and Kubeflow as a machine learning lifecycle management tool. The given architecture responds to the actual requirements of IIoT settings: their velocity of data, heterogeneity of origins, and analysis in real-time. Through Kubernetes dynamic scaling and container orchestration features, fault tolerance and optimization of resources is maintained by the system. Ingestion and transformation of data is carried out using airflow and predictive models can be easily deployed and retrained using Kubeflow. We consider the reliability and performance of the system in a factory environment and suggest the principles of pipeline best practice design to benefit high-scale systems in terms of reliability, elasticity and maintainability. This strategy has shown great prospects of organizations that intend to implement analytics and machine learning in their industrial sectors to use open-source, large-scale infrastructure.

Keywords: Industrial IoT (IIoT), Kubernetes, Apache Airflow, Kubeflow, Data Engineering Pipelines, Machine Learning, Workflow Orchestration, Real-Time Analytics, Scalability, Edge-to-Cloud Infrastructure.

I. INTRODUCTION

Industrial Internet of Things (IIoT) has caused an explosion in the creation of very high volume and velocity of sensor and machine data in manufacturing, energy and logistics industries. Such time-based data feeds can potentially open valuable predictive maintenance, resource-managed, quality, and safety control opportunities. The realization of these objectives, however, requires the existence of powerful, scalable and automated data engineering pipelines performing the task of ingesting, processing, and analyzing data of various sources with a minimal latency and high reliability. [1]

With the current developments in cloud-native computing, the design of resilient data workflows based on Kubernetes-based microservices, container orchestration, and distributed data processing frameworks has become another area of opportunity. Kubernetes provides an infrastructure which is horizontally scalable and highly available to deploy containerized applications in the industrial settings that exhibit both workload elasticity and fault tolerance. In this ecosystem, Apache Airflow and Kubeflow have grown to be also two important elements to coordinate data pipelines and machine learning (ML) workflows, respectively.

The paper aims to:

- Indicate how the traditional industrial data pipeline structures limit the capability of managing dynamic, real time IIoT data.

- Suggest the scalable architecture of a Kubernetes-based pipeline to improve the industrial data integrity, availability, and responsiveness through the industrial data lifecycle.
- Show how automated orchestration (Airflow), distributed computing encompassing orchestration (Kubernetes), and distributed learning and orchestration (Kubeflow) facilitated the improvement of IIoT analytics and predictive modeling to enable the ability to focus on prediction.

A. Problem Statement

Classical industrial data pipelines tend to be quite inflexible and build around batch, whereas in IIoT platforms, machines, sensors, and controllers report data with sub-second frequencies. Such systems find it difficult to be horizontally scaled, are not easily modular and do not provide a lot of support in integrating ML-based anomaly detection or forecasting models. In addition, development, deployment, and monitoring of isolated pipeline elements introduce development and deployment bottlenecks and hamper the generation of real-time insights.

B. The importance of Scalable Data Infrastructure in IIoT

The infrastructure built using Kubernetes can enable IIoT organizations to implement elastic and containerized microservices that scale freely depending on the degree of workload to contemporary scales, thus incurring less cost and complexity in operations. Apache Airflow enables data engineers to specify reproducible data-transformation jobs as Directed Acyclic Graphs (DAGs), and Kubeflow is a platform that integrates all aspects of machine learning in a single Kubernetes cluster, namely training, and serving their models, and monitoring. With such technologies, end-to-end industrial data pipelines can be deployed with security, resiliency and without cloud-dependencies, to ensure that data-driven operations are performing well as data volumes scale; as more analytical tasks are requested.

II. BACKGROUND

The data management in an Industrial Internet of Things (IIoT) has become complex and scalable, cloud-native architectures have had to be adopted. The most important change here is Kubernetes, an open-source system based on containerized applications. Originally designed by Google, Kubernetes promises most important capabilities of horizontal scaling, self-healing capabilities, service discoveries as well as isolation of workload. The capabilities make it extremely applicable to IIoT use, where fault tolerance and real-time performance are essential factors, because of volatility of sensor-driven operational data. [2]

In IIoT environments, the data sources are geographically distributed and heterogeneous, including industrial sensors and programmable logic controller (PLCs), on the edge computing node level, and even cloud-facing APIs. Kubernetes can streamline the delivery and activation of the services needed to consume, preprocess and interpret this data through containerization and declarative configuration. It is also adaptable to time-sensitive and safety critical industrial applications because of its native support to service mesh architectures, persistent storage provisioning, and policy-driven autoscaling.



Fig. 1. Kubernetes Cluster Architecture [3]

The tools one uses along with Kubernetes in the data engineering pipeline include Apache Airflow and Kubeflow, both open-source data and machine learning workflow orchestration tools, respectively. Apache Airflow allows specifying involved Directed Acyclic Graphs (DAGs) on which the ETL (Extract, Transform, Load) operation can be scheduled and managed. It enables dynamic pipeline creation, error replacement, tracking, and recording, which makes it preferred to process batches or micro-batches IIoT data.

Kubeflow, as opposed, is a native Kubernetes framework that enables to build and deploy machine learning models. It provides automation of hyperparameter tuning, experiment controlling, model serving as well as version control. It has a core component Kubeflow Pipelines which enables ML developers to create reusable ML pipelines as containerized tasks, making them both reproducible and consistent across deployment strategies on Kubernetes. [4]

In combination, Kubernetes, Airflow, and Kubeflow compose a cohesive and pluggable system of managing the entire IIoT data lifecycle, including ingestion and transformation, model training and deployment. The architecture enables real-time decisions in industrial environments, lowers the operation cost, and enables agility by continuously integrating and delivering analytics pipelines.

Kubernetes provides in-built service discovery, load balancing, automatic rollout, and self-healing, all of which is essential to providing uptime in mission-critical IIoT applications. Moreover, Apache Airflow orchestration tools make it easy to handle complicated task dependency systems, whereas, Kubeflow is highly compatible with the Kubernetes environment, which is used to manage the complete ML process, including data preprocessing and retraining models.

III. PROPOSED PIPELINE ARCHITECTURE

Scalability, modularity and real-time performance are essential in Industrial Internet of Things (IIoT) settings where the systems will have to contend with massive amounts of sensor and machine data. In this section, we introduce a reliable pipeline that utilizes Kubernetes and combines several tools to respectively manage ETL runs and machine learning lifecycle, Apache Airflow and Kubeflow. The architecture is cloud-native and can be used in a continuous processing of data at different levels: edge, fog and cloud. With design principles of microservices and container orchestration, it can achieve fault tolerance, automatic recovery and limitless scaling of resources. [5]

A. Architecture description

The logical pipeline proposed has five steps (1) Data Ingestion, (2) Data Preprocessing, (3) Data Storage, (4) Real-Time Analytics, and (5) Machine Learning Integration. Every layer is a containerized microservice running-in a Kubernetes cluster. Apache Airflow helps maintain the timing of the tasks in the process of data ingestion and data transformation, whereas Kubeflow Pipelines control the pipelines of the ML process, including training, validation, inference. Kubernetes itself guarantees dynamic scaling, service discovery, rolling updates of every service.

In order to give a systematic overview of the fundamental elements and functionalities, Table below describes the use of each tool in the design.

Layer	Core Technologies	Primary Functions
Data Ingestion	MQTT, OPC-UA, Apache Kafka, Airflow DAGs	Capture telemetry from IIoT devices, schedule and trigger ETL jobs
Data Preprocessing	Apache Spark, Python, Airflow, Kubernetes Jobs	Clean, normalize, extract features, batch or micro-batch transformation
Data Storage	InfluxDB, MinIO, TimescaleDB, AWS S3	Persist real-time and historical data; tiered storage (hot/cold)
Real-Time Analytics	Apache Flink, Kafka Streams, Grafana, Superset	Anomaly detection, threshold alerts, sliding-window aggregations
ML Model Integration	Kubeflow, KFServing, TensorFlow Serving, MLflow	Model training, deployment, monitoring, versioning, inference delivery

Table 1. Pipeline layers & Technologies

B. Layers of Pipelines

1) Data ingestion: The collection of the data is initiated at the edge where RSNs collect and relay telemetry data over light weight protocols like MQTT and OPC-UA. Streaming platforms such as Apache Kafka will store incoming information in a buffer to be read separately. Airflow DAGs are specified to execute segmentation jobs at a fixed period of time (e.g. every 5 minutes) or based on triggers on a device (e.g. temperature spike, device restart). Kubernetes scales ingestion services in accordance with the event rates which provides high availability and low latency rates.

2) Data PreProcessing: The data provided by IIoT sensors is usually noisy, incomplete, or in general imprecise. Preprocessing includes deduplication, normalization, time stamp alignment and context enriching. The actions are either executed in Python or Apache Spark and packaged as Kubernetes Jobs. Airflow coordinates the preprocessing DAGs, and each job can be executed in a separate and restricted pod. The stages are connected by intermediate datasets transferred across stages with the help of shared Persistent Volumes or Dynamically-provisioned object storage buckets organized by Kubernetes.

3) Data Storage: The storage tier is meant to accommodate both operational and archival cases. The hot data are stored in optimized databases which are structured with real-time capabilities including InfluxDB or TimescaleDB that enable the quick query, and visualization. Cold data Downloads like long term machine logs or historical maintenance data are stored in distributed object systems like MinIO or S3. This two-tiered approach allows cost effective storage that does not affect the retrieval speed of its mission-important metrics. The k8s allows CSI (Container Storage Interface) driver abstraction and provisioning of storage backends.

4) Real Time Analytics: Data is streamed, processed on the fly by an application like Apache Flink or Kafka Streams, which run in the form of Stateful Sets on Kubernetes, or Deployments that offer unlimited scalability. These engines are used in supporting complex events processing, alert generation and windowed aggregations. The metrics that are processed are displayed in Grafana dashboards or in the information systems that control the functioning of the system in order to have automated feedback. In the manufactures and utility industries, real-time analytics enhances situation awareness, early warning and predictive alerts

5) ML Model Integration: The last layer is ML lifecycle automation powered by Kubeflow Pipelines which defines the tasks including data loading, feature selection, model training, hyper parameter tuning, validation, and serving. Pipelines are containerized and run as step-based pods within the Kubernetes environment. After training the models are ready to be deployed by a KFServing or TensorFlow Serving system that provides inference endpoints via REST/gRPC. Owing to Prometheus, Tensorboard, and MLflow, performance metrics in terms of accuracy, latency, and concept drift are being monitored. There are Airflow triggers that can be applied in order to sensor the models automatically or when the shifts in data are significant.

C. Security and Interoperability of Systems

Such architecture ensures the unity of CI/CD pipelines with the help of GitOps tools, such as ArgoCD or Flux, and enables the declarative approach to infrastructure or ML models upgrading. Security and compliance is enforced by Kubernetes RBAC, network policies as well as namespace isolation. Service meshes (e.g. Istio) improve the communication between services by adding telemetry, retries, and mTLS-encryption. Prometheus is used to get observability of metrics, Fluentd/Elasticsearch to get logs and Grafana to get dashboards.

D. Edge and Fog Computing coupling

The proposed architecture can also be incorporated with edge and fog computing layers meant to enhance real-time responsiveness further and minimize cloud latency. Initial filtering, anomaly detection or compression may be done on edge nodes, which are located near the IIoT devices, and such edge nodes are operated through K3s (a lightweight distribution of Kubernetes). More capable and centrally placed fog nodes, named by Cisco as fog hubs, can work to act as an intermediary aggregating data and performing time-sensitive analytics and sending selected information on to the Kubernetes cluster in the cloud. This distributed architectural expansion provides reduced bandwidth utilization, improved fault tolerance and better protection of time-sense-critical industrial process. In intermittently connected remote installations at distant locations like offshore platforms or mining facilities such decentralization is especially relevant.

A combination of these open-source technologies allows the proposed pipeline to be scalable, maintainable, and fully automated data infrastructure, specialized in industrial-scale analytics. [6]



Fig. 2. End-to-End ML Pipeline Workflow [7]

IV. SCALABILITY AND PERFORMANCE

The Industrial Internet of Things (IIoT) ecosystems work under varied, dynamic, and in many cases, mission-critical assumptions. These settings produce humongous telemetry data and at different frequencies which may depend on production litany, weather, or periods of maintenance. In this sense, horizontal scalability and real-time performance are equally important to sustaining ongoing processes and predictive data analytics. The Kubernetes-based architecture proposed in the paper is specifically built with consideration of such constraints and designed to solve the following issues, as it provides a flexible autoscaling, adaptive workflow orchestration, and observation-based improvements, relying on mature open-source tools, such as Apache Airflow and the Kubeflow Pipelines. [8]

A. Resource orchestration and Kubernetes-Native Autoscaling

By the infrastructure level, Kubernetes provides dynamic scaling that plays a critical role in the computation requirements of a distributed pipeline. The Horizontal Pod Autoscaler (HPA) scales the replica of pods of stateless services (e.g. MQTT consumer or the Kafka-based ingestion modules) using real-world consumption measurement sensors of CPU or memory usage. Example: in case there is a factory-wide restart and all the sensor data comes flooding into the pipeline, HPA can spin up ingestion pods on-the-fly to mitigate its effect, without losing data or causing job backlogging.

The Cluster Autoscaler, together with HPA, helps to make sure that the underlying compute nodes are managed elastically through the launching of new tasks, virtual machines, or containers, supporting more pods. It allows organizations to fulfill high service level agreements (SLAs) and not over allocate infrastructure at off-peak times.

In cases where the workloads require memory intensive tasks, e.g. model training in Kubeflow, or distributed data joins in Spark, Vertical Pod Autoscaler (VPA) will be necessary. It also automates pod resource constraints depending on past as well as current consumption to enhance consistency in performance without resulting in wastage of infrastructure. VPA improves robust performance in rapidly changing environments by configuration level tuning of memory and CPU allocations to long-running jobs.

Node affinity rules and taints/tolerations are applied in order to make such scaling policies work within heterogeneous environments. These make sure that time-sensitive or GPU-demanding tasks, like inference services or time-sensitive anomaly detection modules are served by properly configured machines with additional I/O or machine-specific AI accelerators.

B. Scheduling and Smart Resources Allocation

Every pipeline stage specifies its own resource request and constraints, in Kubernetes manifest. This allows the Kubernetes scheduler to take smart decisions on where to place pods in nodes and to optimum bin-packing as a general goal, but without causing the node to become overloaded. One of them is that these systems can be configured so that important workloads can prioritize over background or batch jobs thus important services will always have the resources they need when they need it since latency sensitive services are sensitive.

The Kubernetes Pod Operator in Apache Airflow containerizes each ETL task into its own pod with resource scoping, making it quite reproducible and with no noisy neighbor problems. In Kubernetes, with the help of Spark Operator, Spark applications may scale their executors in size in response to the amount of data arriving or depending on the requirements of transformations. Such dynamic behavior side-steps the need of pre-tuned cluster sizes and allows just-in time resource provisioning of batch workloads. [9]

Regarding storage of data and throughput, Kubernetes enables support of Container Storage Interface (CSI) drivers to mount dynamically provisioned volumes. Telemetry that needs low latency access, such as time sensitive data, is cached on SSDs with high user access speeds, such as 1Gb/s, whereas bulk or storage data is stored using an object storage system such as MinIO or Amazon S3. Such a tiered approach guarantees high performance as regards to speed of retrieving data when executing analytics, but without paying excessive costs of storing cold data on high-powered volumes.

C. Resilience and workflow Optimization

Task logic Airflow and Kubeflow Pipelines support conditional task logic, which allows the architecture to respond to changing system conditions and dataset conditions. As an example, a retraining job can be invoked only when the observed accuracy dips below some pre-specified accuracy or a concept drift is identified in the incoming features. In like manner, data transformation steps may be bypassed should schema checks or quality checks become failed, freeing compute resources and making the pipeline run faster.

Streaming systems are based on stateful services such as Apache Flink and Kafka Streams that are installed on the machines and have distributed checkpointing and failover logic included. This provides uniform state recovery in case of pod failures or nodes failures which is vital to real-time applications like energy grid surveillance, predictive digestion in the manufacturing business, fault delirium beadings in energy delivery networks.

The system is also fault resistant in the infrastructure layer: Kubernetes checks whether a container is unhealthy using readiness and liveness probes; and the pattern of rolling deployment makes sure that updates do not disrupt active services.

D. Feedback Based Optimization

The high performance and availability cannot be maintained without regular checking. The architecture is completely instrumented and has end-to-end visibility of Prometheus, Grafana, and Fluentd/Elasticsearch. Prometheus scrapes graphs like the pod CPU pod usage and latency, message backlog and DAG execution time. These are represented through Grafana dashboards, through which the operations teams can observe the state of health of the pipelines.

Besides, autoscaling policies are based on metrics, as well. As an example, imagine that average message lag in a Kafka topic may be above a threshold value for longer than 2 minutes, then, new ingestion consumers may be automatically spawned. On the same note, task managers of Flink cluster may be further deployed to

the cluster using Kubernetes Stateful Sets, in case the latency of the Flink processing is longer than the window duration. Fluentd picks up airflow execution logs and the success/failure of tasks to be indexed to enhance the process of debugging and incident response times. [10]
In order to make sure that we get proactive alerting, we set Alert manager to work with Prometheus in order to alert operators whenever thresholds are violated or services are degraded through Slack, mail, or SMS. This short cycle feedback guarantee that pipeline components are sensitive and recoverable, even during unforeseen state of load.

Pipeline Stage	Autoscaling/Elasticity Features	Performance Enhancements
Data Ingestion	HPA, Kafka consumer scaling	Batching, message queue depth monitoring, retry logic
Data Preprocessing	Spark executor autoscaling, VPA	DAG parallelism, in-memory caching, CSI volume tuning
Data Storage	CSI drivers, tiered hot/cold storage layers	SSD volumes for hot data, S3-compatible object storage for archival
Real-Time Analytics	Flink Stateful Sets + Checkpointing	Sliding-window aggregation, dynamic operator parallelism
ML Model Management	KFServing HPA, GPU-based node scheduling	Conditional training, lightweight inference endpoints
Monitoring & Alerts	Prometheus + Grafana + Alert Manager	Resource-based scaling, feedback loops for real-time adaptation

Table 2. Scalability Strategies by Stage

V. CONCLUSION

The Industrial Internet of Things (IIoT) will create ever-increasing data volumes with high variety, brought by diverse, heterogeneous data, and velocity, in the form of telemetry streams, the necessity of distributed, autonomous, and elastic data engineering pipelines to ingest, process, and analyze data such as telemetry streams efficiently is rapidly growing. The architecture described in this paper represents a modular and cloud-native data pipeline using Kubernetes and integrates Apache Airflow and Kubeflow to perform data process orchestration and management of their machine learning lifecycles, respectively.
The proposed pipeline is elastic, fault-tolerant, and has little latency via dynamic auto scaling, container orchestrating, and workflow optimization. Apache Airflow allows one to do reproducible ETL with DAGs, and Kubeflow will allow us to automate retraining and deployment of the ML models in the same Kubernetes environment. This architecture allows an industrial domain to bask in predictive analytics, condition-based monitoring, real-time feedback loops through the use of open-source and cloud agnostic systems that are necessary to support operational effectiveness and reducing risk.
A direction of future research is more tightly related integrations with edge computing frameworks so that on-device inference and federated learning can be used to do privacy-preserving applications. Even such simple enhancements as scheduling using reinforcement learning to improve the intelligence of pipelines, incorporation of event-driven frameworks such as K-native, could further support reactivity and efficiency. Moreover, policy-based data governance and security framework at the Kubernetes cluster would also prove essential to regulatory compliance as the IIoT applications achieve geographic and sector distribution.

REFERENCES:

1. T.-t. N.-t. N.-t. N.-t. N. Thanh-tung nguyen, "horizontal pod autoscaling in kubernetes for elastic container orchestration," mdpi, 2020.
2. R. B. Maria a. Rodriguez, "containers orchestration with cost-efficient autoscaling in cloud computing environments," https://arxiv.org/, 2018.

3. Platform9, "kubernetes concepts and architecture," platform9, 2019. [online]. Available: https://platform9.com/blog/kubernetes-enterprise-chapter-2-kubernetes-architecture-concepts/.
4. R. B. X. Y. Tao chen, "a survey and taxonomy of self-aware and self-adaptive cloud autoscaling systems," arxiv.org, 2018 .
5. E. Bisong, "kubeflow and kubeflow pipelines," researchgate, 2019.
6. T. R. A. K. R. S. H. H. V. M. Jeyhun karimov, "benchmarking distributed stream data processing systems," arxiv.org, 2019.
7. Y. Haviv, "kubernetes, the open and scalable approach to ml pipelines," medium, 2019. [online]. Available: https://medium.com/data-science/kubernetes-the-open-and-scalable-approach-to-ml-pipelines-1e972a965f0d.
8. J. S. V. M. Quoc-cuong to, "a survey of state management in big data processing systems," arxiv.org, 2018.
9. F. B. S. R. G. Hai dinh-tuan, "maia: a microservices-based architecture for industrial data analytics," arxiv.org, 2019.
10. S. C. Y. S. Anshu shukla, "riotbench: a real-time iot benchmark for distributed stream processing platforms," arxiv.org, 2017.