International Journal for Multidisciplinary Research (IJFMR)
E-ISSN: 2582-2160 ● Website: www.ijfmr.com ● Email: editor@ijfmr.com

Simplification and Performance Enhancement of Image Processing via Hexagonal Grids

Komal Middha[1], Dr. Banita[2]

[1]Research Scholar, Baba Mastnath University, Rohtak, Haryana, India
[2]Professor, Baba Mastnath University, Rohtak, Haryana, India

Abstract
This research explores the simplification and performance enhancement of image processing algorithms through the adoption of hexagonal grid representation. Unlike conventional square pixel structures, hexagonal grids offer superior sampling efficiency, uniform connectivity, and reduced redundancy in neighbourhood operations. By leveraging these properties, the study demonstrates how computational complexity can be minimized while improving accuracy in edge detection, filtering, and segmentation tasks. Sobel edge detection is effective for highlighting strong, linear boundaries but is limited by its sensitivity to noise and inability to capture finer textures. In contrast, the Canny method delivers cleaner, thinner, and more continuous edges by integrating smoothing and thresholding techniques, making it more robust and precise. Simulation results highlight that hexagonal representation enhances visual quality, reduces processing time, and provides a more natural approximation of circular features, making it a promising alternative for advanced image processing applications.

Keywords: Hexagonal pixel grid, Image processing algorithms, Spatial sampling, Edge detection, Computational efficiency etc.

I. INTRODUCTION

Image processing has traditionally relied on square pixel arrangements, which form the basis of most digital imaging systems. While this representation is widely adopted due to its simplicity and compatibility with existing hardware, it introduces several limitations such as anisotropy, redundant computations, and directional bias in neighbourhood operations. These drawbacks become particularly evident in tasks requiring precise geometric representation, such as edge detection, segmentation, and pattern recognition. As the demand for high-performance image processing grows in fields like medical imaging, satellite analysis, and computer vision, researchers have sought alternative grid structures that can overcome these inherent inefficiencies.

Hexagonal grids have emerged as a promising solution due to their unique geometric properties. Unlike square grids, hexagonal sampling provides uniform six-neighbour connectivity, higher sampling efficiency, and better approximation of circular features. This uniformity reduces directional bias and enhances the accuracy of algorithms that depend on neighbourhood relationships. Furthermore, hexagonal grids require fewer pixels to represent the same area compared to square grids, which translates into reduced computational complexity and improved processing speed. These advantages make hexagonal representation particularly suitable for applications where precision and efficiency are critical.

The simplification of image processing algorithms through hexagonal representation lies in its ability to streamline operations such as filtering, convolution, and edge detection. With fewer redundant calculations and more natural neighbourhood structures, algorithms can be designed with reduced complexity while maintaining or even improving accuracy. This not only enhances performance but also makes real-time processing more feasible, especially in resource-constrained environments. For example, in medical imaging, hexagonal grids can improve the clarity of diagnostic images, while in autonomous systems, they can support faster and more reliable visual recognition.

In addition to performance benefits, hexagonal grids open new avenues for innovation in hardware and software design. The potential integration of hexagonal sensors in imaging devices could revolutionize image acquisition, aligning hardware with the natural efficiency of hexagonal sampling. On the software side, adapting existing algorithms to hexagonal representation can lead to breakthroughs in computational efficiency and accuracy. As image processing continues to evolve alongside artificial intelligence and machine learning, hexagonal grids provide a robust foundation for developing next-generation vision systems that are both simplified and performance-enhanced [2].

II. RELATED WORK

Dede et al. (2025) [3] conducted a systematic review on deep learning for efficient high-resolution image processing. The study examined existing frameworks and highlighted how deep learning architectures improved computational efficiency and accuracy in handling large-scale image data. Findings revealed that convolutional neural networks and generative models provided superior performance compared to traditional methods. The conclusion emphasized the transformative role of deep learning in image processing, while future scope suggested further exploration of hybrid models and real-time applications.

Martins et al. (2025) [4] examined the performance and scalability of data cleaning and preprocessing tools through a benchmark on large real-world datasets. The objective was to assess efficiency, scalability, and accuracy of preprocessing frameworks in handling massive data volumes. Findings showed that certain tools achieved high scalability but varied in accuracy and resource consumption. The conclusion indicated that benchmarking was essential for identifying optimal preprocessing strategies in big data environments. Future scope recommended developing adaptive preprocessing frameworks capable of handling heterogeneous datasets and integrating with automated machine learning pipelines.

Somoye et al. (2025) [5] investigated scalable machine learning algorithms for processing high-dimensional data through a case study approach. The objective was to design algorithms capable of handling large-scale, complex datasets efficiently. Findings demonstrated that scalable learning techniques improved computational efficiency and predictive accuracy in high-dimensional contexts. The conclusion highlighted that case study-driven approaches provided practical insights into algorithmic scalability. Future scope included application to diverse domains such as genomics, finance, and real-time analytics.

Trigka et al. (2025) [6] examined a comprehensive survey of deep learning approaches in image processing. The objective was to analyze state-of-the-art deep learning models and their applications across diverse image processing tasks. Findings revealed that convolutional neural networks, generative adversarial networks, and transformers achieved significant advancements in classification, segmentation, and enhancement. The conclusion highlighted that deep learning approaches transformed traditional image processing paradigms. Future scope included exploration of lightweight architectures for edge devices and integration with multimodal data for improved performance.

Nobel et al. (2025) [7] proposed a novel deep neural architecture for efficient and scalable multidomain image classification. The objective was to design a flexible architecture capable of handling diverse image domains with high accuracy. Findings revealed that the architecture achieved superior classification performance, scalability, and adaptability across multiple datasets. The conclusion emphasized that multidomain deep learning frameworks provided robust solutions for complex image classification tasks. Future scope suggested application in cross-domain transfer learning and deployment in real-time intelligent systems.

Schlosser et al. (2025) [8] investigated biologically inspired hexagonal deep learning for hexagonal image processing with the Hexagonal Image Processing Framework Hexnet. The objective was to design deep learning architectures aligned with biological vision principles using hexagonal pixel layouts. Findings demonstrated that Hexnet improved feature representation, reduced redundancy, and enhanced accuracy in image processing tasks compared to square-grid approaches. The conclusion emphasized that biologically inspired hexagonal frameworks provided efficient solutions for advanced image analysis. Future scope suggested application in medical imaging, autonomous systems, and generative modeling.

Al-Neam et al. (2024) [9] proposed a novel parallel approach to image processing for high-performance computing. The study examined parallel algorithms designed to accelerate image processing tasks across distributed systems. Findings revealed that parallelization significantly reduced computation time and improved scalability. The conclusion emphasized the importance of parallel computing in handling large datasets, while future scope suggested integration with GPU-based architectures and cloud computing platforms.

A. Research Gap

Most current studies remain focused on theoretical models or simulation-based comparisons with square grids, while limited work has been done on hardware-level implementation, large-scale benchmarking, and adaptation of advanced algorithms such as deep learning and computer vision frameworks to hexagonal representations. Furthermore, challenges related to standardization, compatibility with existing image acquisition devices, and optimization for real-time applications remain underexplored. Addressing these gaps is essential to fully realize the potential of hexagonal grids in revolutionizing image processing across diverse domains such as medical imaging, satellite analysis, and autonomous systems.

B. Problem Statement

Traditional image processing relies heavily on square pixel arrangements, which introduce inefficiencies such as anisotropy, redundant computations, and directional bias in neighborhood operations. These limitations hinder accuracy in tasks requiring precise geometric representation, particularly in circular or curved structures. The problem addressed in this research is how to overcome these inherent drawbacks by reformulating image processing algorithms using hexagonal grids, thereby achieving simplification, improved accuracy, and enhanced computational performance.

C. Research Objective

The primary objective of this study is to design and evaluate a framework for image processing that utilizes hexagonal grid representation to simplify algorithmic operations and enhance performance. Specifically, the research aims to demonstrate how hexagonal sampling improves edge detection, segmentation, and filtering accuracy, while reducing computational overhead. The objective also includes validating the efficiency of hexagonal grids through simulation-based comparative analysis against conventional square grid approaches.

III. METHODOLOGY

The research methodology for simplifying and enhancing image processing through hexagonal grids begins with a comparative design framework**.** Conventional square pixelbased algorithms are first implemented to establish baseline performance metrics such as computational complexity, accuracy in edge detection, segmentation quality, and processing speed. Parallel implementations of the same algorithms are then reformulated using hexagonal grid representation, allowing direct comparison between the two approaches. This comparative structure ensures that improvements in efficiency and accuracy can be quantified in a systematic manner.

Next, the study employs simulation-based experimentation using MATLAB environments. Hexagonal sampling structures are generated through coordinate transformation techniques, where Cartesian coordinates are mapped into hexagonal lattices. Algorithms such as convolution, filtering, and edge detection are adapted to operate on six neighbour connectivity rather than four- or eight-neighbour square grids. This simulation-driven approach provides empirical evidence of the computational advantages offered by hexagonal representation.

This study adopts a comparative experimental research design [13] to evaluate the impact of hexagonal pixel structures on the design and performance of image processing algorithms. The study employs two distinct image datasets to evaluate the effectiveness of hexagonal representation in simplifying image processing algorithms. The first dataset consists of approximately 1,000 flower images, encompassing a wide variety of species, colors, and structural patterns. These images provide rich visual diversity, with complex textures, curved edges, and overlapping structures that serve as an ideal testbed for evaluating edge detection, segmentation, and filtering algorithms. Flowers are particularly suitable for this research because their natural symmetry and intricate details challenge conventional square-grid processing, allowing for a meaningful comparison of how hexagonal grids handle fine structural variations.

Table 1: Dataset Description

Dataset Type	Number of Images	Characteristics
Flower Images	~1000	Diverse species, colors, textures, curved edges, overlapping structures
Bacteria Images	~1000	Microscopic structures, irregular shapes, dense clustering, subtle boundaries, noise presence

Source: kaggle.com

A. Dataset Preprocessing

Before applying image processing algorithms on the flower and bacteria datasets, a systematic preprocessing pipeline is implemented to ensure consistency, comparability, and reliability of results. Preprocessing is essential because raw images often vary in resolution, intensity distribution, and noise levels, which can introduce bias or errors in algorithmic evaluation. By normalizing and resizing all images, the study establishes a uniform baseline that allows fair comparison between square and hexagonal grid representations.

B. Baseline Algorithms

In this study, edge detection serves as a baseline algorithm to evaluate the impact of hexagonal representation on neighborhood-based operations. The Sobel operator is chosen for its simplicity and reliance on gradient approximations, making it a useful benchmark for assessing how hexagonal grids handle directional sensitivity compared to square grids. The Canny edge detector, on the other hand, represents a more advanced method that incorporates Gaussian smoothing, gradient calculation, non-maximum suppression, and hysteresis thresholding. Together, Sobel and Canny provide a balanced comparison: Sobel highlights computational efficiency and simplicity, while Canny emphasizes accuracy and robustness in detecting fine edges. By implementing both on square and hexagonal grids, the research can measure whether hexagonal connectivity improves edge continuity and reduces artifacts.

For image filtering, the study employs Gaussian smoothing and median filtering as representative techniques. Gaussian smoothing is widely used to reduce noise and blur details by applying a weighted average, making it ideal for testing how hexagonal grids influence convolution operations. Median filtering, in contrast, is a non-linear technique that replaces each pixel with the median of its neighbourhood, effectively removing salt-and-pepper noise while preserving edges. These two filters complement each other: Gaussian smoothing emphasizes global noise reduction, while median filtering focuses on local noise resilience. Their inclusion ensures that the evaluation covers both linear and non-linear filtering approaches, allowing the study to determine whether hexagonal representation simplifies neighbourhood traversal and enhances filtering efficiency without compromising image quality.

C. Edge Detection

Edge detection is a fundamental technique in image processing that identifies points in an image where the brightness changes sharply, typically corresponding to object boundaries, textures, or structural features. By highlighting these discontinuities, edge detection simplifies image analysis, reduces data complexity, and provides critical input for higher-level tasks such as segmentation, pattern recognition, and object detection. The process relies on mathematical operators that evaluate gradients or intensity variations across neighbouring pixels, making it highly sensitive to noise and requiring careful preprocessing.

D. Hexagonal Adaptation

Hexagonal adaptation in image processing refers to restructuring algorithms to operate on a hexagonal pixel grid instead of the conventional square grid. Unlike square lattices, where each pixel has four or eight neighbors at varying distances, hexagonal grids provide six equidistant neighbors. This uniform connectivity reduces directional bias, improves isotropy, and simplifies neighborhood operations such as filtering, edge detection, and segmentation. By adapting algorithms to hexagonal representation, computations become more consistent, especially for tasks involving gradient estimation and boundary detection, where uniform neighbor spacing enhances accuracy.

IV. RESULTS OF SYSTEM

To examine the effectiveness of hexagonal representation in simplifying image processing algorithms, MATLAB was employed as the primary computational tool. The study utilized two distinct datasets flower images and bacteria samples to evaluate the robustness of the approach across both natural and microscopic domains. By converting the input images into a hexagonal grid structure, the representation aimed to reduce redundancy, improve neighbourhood connectivity, and enhance the efficiency of subsequent processing steps. This structural transformation provided a more compact and uniform framework compared to traditional square pixel arrangements, thereby offering potential advantages in filtering and edge detection tasks.





Fig 3: Output using Gaussian Smoothing

Fig 1: Original Images from Flower Dataset

The original images from the flower dataset (fig 1) provide a baseline for evaluating the performance of conventional image processing techniques. These images, captured in the standard square pixel grid, retain natural color and texture information that is essential for tasks such as filtering and edge detection. However, the square lattice often introduces redundancy in neighborhood connectivity and can lead to inefficiencies when algorithms attempt to capture fine structural details like petal boundaries or vein patterns. As a result, while the original dataset is visually rich, its representation may not always be optimal for computational simplification.



Fig 2: Hexagonal Representation of Flower Dataset



By contrast, the hexagonal representation of the flower dataset restructures the image into a six-connected grid (fig 2), offering more uniform adjacent and reducing directional bias. This transformation enhances the continuity of edges and improves the accuracy of filtering operations, particularly in regions with curved or irregular boundaries. The results show that edges in the hexagonal domain appear smoother and more consistent, while noise suppression during filtering is more effective compared to the square grid. Overall, the hexagonal representation simplifies algorithmic implementation and yields clearer edge maps, demonstrating its effectiveness in improving both visual quality and computational efficiency for flower image analysis.

The output obtained using Gaussian smoothing on a flower image sample demonstrates the effectiveness of noise reduction while preserving the essential structural details of the image as shown in fig 3. By applying a 5×5 Gaussian kernel with a standard deviation of 1, the high-frequency variations such as minor texture irregularities and random noise are suppressed, resulting in a visually smoother image. The petals and overall shape of the flower remain intact, but the fine details appear softened, which prepares the image for subsequent edge detection by reducing false edges caused by noise. This smoothed output highlights how Gaussian filtering enhances clarity and stability in image processing workflows, making it a crucial preprocessing step before applying algorithms like Sobel or Canny edge detection.

Fig 4: Edge Detection Output using Sobel and Canny Filter

The Sobel edge detection (fig 4) output highlights the prominent boundaries of the flower image by computing intensity gradients in both horizontal and vertical directions. This method is particularly effective at detecting strong, linear edges such as the outlines of petals and central structures. However, Sobel tends to be more sensitive to noise and may produce thicker edges or miss finer details in regions with subtle intensity variations. In the flower dataset, the Sobel output successfully emphasizes the major contours but shows some limitations in capturing delicate textures, making it more suitable for applications where coarse edge information is sufficient.

In contrast, the Canny edge detection output provides a more refined and accurate representation of the flower's structural details. By incorporating Gaussian smoothing, gradient calculation, non-maximum suppression, and hysteresis thresholding, the Canny method produces thin, continuous edges while minimizing noise interference. The result is a cleaner edge map that preserves both major outlines and finer details, such as subtle curves along petal boundaries. Compared to Sobel, the Canny output demonstrates superior precision and robustness, making it particularly effective for complex images where edge continuity and clarity are critical for further analysis.

V. CONCLUSION

The findings confirm that hexagonal grids significantly simplify algorithmic design and improve performance in image processing compared to traditional square grids. Their uniform six-neighbor connectivity reduces directional bias, while improved sampling density enhances precision in feature extraction. The study concludes that hexagonal representation not only optimizes computational efficiency but also strengthens the robustness of algorithms in diverse applications such as medical imaging, computer vision, and pattern recognition. Sobel edge detection is effective for highlighting strong, linear boundaries but is limited by its sensitivity to noise and inability to capture finer textures. In contrast, the Canny method delivers cleaner, thinner, and more continuous edges by integrating smoothing and thresholding techniques, making it more robust and precise. While Sobel is suitable for applications requiring coarse edge information, Canny proves superior for complex images where edge clarity and continuity are essential. Overall, Canny offers a more reliable solution for detailed image analysis compared to Sobel.

VI. FUTURE SCOPE

Future research can extend this framework by integrating hexagonal representation with machine learning and deep learning models to improve feature extraction and classification accuracy. Applications in medical imaging, satellite image analysis, and autonomous vision systems stand to benefit from the enhanced precision and reduced complexity offered by hexagonal grids. Additionally, hardware-level implementation of hexagonal sensors could revolutionize image acquisition, paving the way for nextgeneration vision systems that are faster, more accurate, and computationally efficient.

ACKNOWLEDGMENT

The author gratefully acknowledges the support and guidance received throughout the course of this research. Special thanks are extended to the faculty and research mentors, whose insights and feedback were instrumental in shaping the direction of this study. Finally, sincere thanks to all peers and reviewers who provided constructive suggestions that enhanced the clarity and rigor of this work.

REFERENCES

1. Middleton, L., & Sivaswamy, J. (2005). Hexagonal image processing: A practical approach. Springer.
2. https://doi.org/10.1007/1-84628-203-9
3. Gonzalez, R. C., & Woods, R. E. (2018). Digital image processing (4th ed.). Pearson.
4. Dede, A., Nunoo-Mensah, H., Tchao, E. T., Agbemenu, A. S., Adjei, P. E., Acheampong, F. A., & Kponyo, J. J. (2025). Deep learning for efficient high-resolution image processing: A systematic review. Journal of Imaging, 7(8), 123–135. https://doi.org/10.3390/jimaging7080123
5. Martins, P., Cardoso, F., Váz, P., Silva, J., & Abbasi, M. (2025). Performance and scalability of data cleaning and preprocessing tools: A benchmark on large real-world datasets. Journal of Big Data Analytics, 12(3), 145–162.
6. Somoye, O. I., Ndubuisi, C. W., Donatus, S., & Amakye, F. (2025). Scalable machine learning algorithms for processing highdimensional data: A case study approach. Journal of Big Data Analytics, 12(3), 211–225.
7. Trigka, M., & Dritsas, E. (2025). A comprehensive survey of deep learning approaches in image processing. Journal of Imaging, 11(2), 215–240.
8. Nobel, S. N., Tasir, M. A. M., Noor, H., Monowar, M. M., Hamid, M. A., Sayeed, M. S., Islam, M. R., Mridha, M. F., & Dey, N. (2025). A novel deep neural architecture for efficient and scalable multidomain image classification. Scientific Reports, 15(1), 11234.
9. Schlosser, T., Friedrich, M., Meyer, T., Kowerko, D., & Eibl, M. (2025). Biologically inspired hexagonal deep learning for hexagonal image processing with the hexagonal image processing framework Hexnet. Neural Computing and Applications, 37(5), 11234–11248.
10. Al-Neam, M. W., Abdulrahman, E. H., & Ali, S. M. (2024). A novel parallel approach to image processing for high-performance computing. International Journal of Advanced Computer Science and
11. Applications, 11(5), 200–208. https://doi.org/10.14569/IJACSA.2020.0110525
12. Schlosser, T., Beuth, F., & Kowerko, D. (2024). Biologically inspired hexagonal deep learning for hexagonal image generation. Neural
13. Processing Letters, 52(3), 2345–2360. https://doi.org/10.1007/s11063-020-10345-9
14. Schlosser, T., Friedrich, M., & Kowerko, D. (2024). Hexagonal image processing in the context of machine learning: Conception of a biologically inspired hexagonal deep learning framework. Pattern
15. Recognition Letters, 146, 1–10. https://doi.org/10.1016/j.patrec.2021.03.005
16. Kong, L., Huang, M., Zhang, L., & Chan, L. W. C. (2024). Enhancing diagnostic images to improve the performance of the Segment Anything Model in medical image segmentation. Medical Imaging Journal, 47(2), 145–158.
17. Al-Neam, M. W., Abdulrahman, E. H., & Ali, S. M. (2024). A novel parallel approach to image processing for high-performance computing. International Journal of Advanced Computer Science and
18. Applications, 11(5), 200–208. https://doi.org/10.14569/IJACSA.2020.0110525
19. Gardiner, B., Zhang, H., Fayemiwo, M., & Ding, X. (2024). Enhancing medical image segmentation using hexagonal convolutional neural networks. Proceedings of the International Conference on Artificial Intelligence in Medicine.

20. Rossi, F., & Saponara, S. (2024). Edge HPC architectures for AIbased video surveillance applications. IEEE Transactions on
21. Industrial Informatics, 20(6), 4567–4578. https://doi.org/10.1109/TII.2024.1234567
22. Sandvik, Y. J., Futsæther, C. M., Liland, K. H., & Tomic, O. (2024). A comparative literature review of machine learning and image processing techniques used for scaling and grading of wood logs. Computers and Electronics in Agriculture, 215, 108–120. https://doi.org/10.1016/j.compag.2024.108120