

Design and Performance Analysis of Maximum Power Point Tracking (MPPT) Algorithms for Solar Photovoltaic Systems

Ms. Samrudhi Namdev Savant¹, Ms. Sakshi Anand Magadum²,
Ms. Asmita Sanjay Chirmure³, Ms. Asmita Suresh Walkar⁴,
Ms. Ashwini Subhash Patil⁵

^{1,2,3,4}Student, Electrical Engineering Department, Sant Gajanan Maharaj Rural Polytechnic, Chinchewadi Site Mahagaon

⁵Madam, Electrical, Sant Gajanan Maharaj Rural Polytechnic Mahagaon

Abstract

The efficiency of solar photovoltaic (PV) systems is highly dependent on environmental conditions such as solar irradiance and ambient temperature. Because PV modules exhibit non-linear voltage-current (I-V) characteristics, extracting the maximum available power requires active electronic tracking. This paper presents a comprehensive study of Maximum Power Point Tracking (MPPT) systems, focusing on the integration of a DC-DC boost converter controlled by advanced tracking algorithms. A comparative analysis of the Perturb and Observe (P&O) and Incremental Conductance (INC) methods is discussed to evaluate their tracking speed, steady-state oscillations, and overall efficiency under varying weather conditions.

Keywords: Maximum Power Point Tracking, Solar Photovoltaic, DC-DC Converter, Perturb and Observe, Incremental Conductance, Renewable Energy.

1. Introduction

Solar energy is one of the most abundant and sustainable renewable energy sources available. However, the energy conversion efficiency of standard PV panels is relatively low, typically ranging from 15% to 20%. Furthermore, the output power fluctuates significantly due to the non-linear relationship between voltage and current, which shifts continuously with changing solar insolation and temperature.

To ensure the PV system operates at its peak efficiency at all times, an MPPT controller is placed between the PV array and the load (or grid inverter). The MPPT system continuously adjusts the electrical operating point of the modules to match the Maximum Power Point (MPP) on the P-V curve. This paper explores the theoretical framework of PV modeling, the design of the power electronic interface, and the logic behind standard tracking algorithms.

2. Mathematical Modeling of the PV Cell

A solar cell can be modeled as a current source in parallel with a diode, along with series and shunt resistances to account for internal losses. The output current I of the PV cell is defined by the following

equation:

$$I = I_{ph} - I_s \left[\exp \left(\frac{q(V + IR_s)}{kTA} \right) - 1 \right] - \frac{V + IR_s}{R_{sh}}$$

- I_{ph} = Photocurrent (generated by solar insolation)
- I_s = Diode reverse saturation current
- V = Output voltage of the cell
- q = Electron charge (1.602×10^{-19} C)
- k = Boltzmann's constant (1.381×10^{-23} J/K)
- T = Cell temperature in Kelvin
- A = Diode ideality factor
- R_s and R_{sh} = Series and shunt resistances respectively

The performance of the panel is often evaluated using the Fill Factor (FF), which measures the "squareness" of the I-V curve:

$$FF = \frac{V_{mp} I_{mp}}{V_{oc} I_{sc}}$$

Where V_{mp} and I_{mp} are the voltage and current at maximum power, V_{oc} is the open-circuit voltage, and I_{sc} is the short-circuit current.

3. The Role of the DC-DC Converter

To track the MPP, the impedance of the load must be dynamically matched to the internal impedance of the PV source. This is achieved using a DC-DC converter (such as a Buck, Boost, or Buck-Boost converter).

For grid-tied or battery-charging applications, a Boost Converter is commonly used to step up the PV voltage. The MPPT controller achieves impedance matching by varying the duty cycle (D) of the high-frequency switching element (usually a MOSFET or IGBT) inside the converter. Ensuring proper switchgear and protection mechanisms (like fast-acting fuses or overvoltage relays) at this converter stage is critical to protect the downstream components from voltage spikes during rapid irradiance changes.

Project Diagram



4. MPPT Control Algorithms

Several algorithms exist to adjust the duty cycle of the converter. The two most prominent are:

4.1 Perturb and Observe (P&O)

The P&O algorithm operates by periodically perturbing (adjusting) the terminal voltage of the PV panel and comparing the current power output with the previous power output.

- If $\Delta P > 0$, the perturbation moved the operating point closer to the MPP, so the next perturbation continues in the same direction.
- If $\Delta P < 0$, the operating point moved away from the MPP, so the direction of perturbation is reversed.

While simple to implement, P&O suffers from continuous oscillations around the MPP during steady-state weather conditions.

4.2 Incremental Conductance (INC)

The INC method relies on the fact that the slope of the P-V curve is zero at the MPP ($dp/dv = 0$). It compares the instantaneous conductance (I/V) to the incremental conductance ($\Delta I/\Delta V$).

- At MPP: $\Delta I/\Delta V = -I/V$
- Left of MPP: $\Delta I/\Delta V > I/V$
- Right of MPP: $\Delta I/\Delta V < -I/V$

This method stops perturbing once the MPP is reached, eliminating steady-state oscillations, though it requires more complex control logic.

5. Methodology and Results

(Author's Note: In this section, you will detail your specific project work. Describe whether you simulated the system in MATLAB/Simulink or built a hardware prototype using a microcontroller like an Arduino/ESP32.)

Parameters to highlight in your results:

- The time it takes for the algorithm to locate the MPP from a cold start.
- The system's response to a sudden step-change in solar irradiance (e.g., a cloud passing over).
- The voltage and current waveforms at the input and output of the DC-DC converter.

6. Conclusion

The implementation of an MPPT system is essential for maximizing the economic and operational viability of solar PV installations. The comparative theoretical analysis indicates that while the P&O algorithm offers simplicity and ease of programming, the Incremental Conductance method provides superior stability under rapidly changing environmental conditions. By effectively coupling the PV array to a suitably designed DC-DC converter, the system can continuously extract maximum power, thereby improving the overall energy yield.

References

1. K. H. Hussein, "Maximum Power Point Tracking," 1995.
2. T. Esram & P. L. Chapman, "Comparison of MPPT Techniques," 2007.
3. J. Ahmed & Z. Salam, "Improved P&O MPPT," 2015.
4. Q. Mei et al., "Incremental Conductance MPPT," 2011.
5. S. Selvaraj et al., "Review of MPPT Algorithms," 2023.

6. S. Singh et al., “P&O MPPT using Boost Converter,” 2020.
7. S. Paul & J. Thomas, “ANN-based MPPT,” 2014.
8. E. Kim et al., “Adaptive Incremental Conductance MPPT,” 2020.