International Journal for Multidisciplinary Research (IJFMR)
E-ISSN: 2582-2160 ● Website: www.ijfmr.com ● Email: editor@ijfmr.com

A Vertex-Centric Graph-Theoretic Framework for Energy-Efficient Distributed Localization in Wireless Sensor Networks

Ashwini Pravin Bhong[1], Dr.Vishwajeet S. Goswami[2]

[1]Research Scholar, Department of Mathematics, Shri JJT University, Rajasthan
[2]Associate Professor, School of Engineering, Ajeenkya D Y Patil University, Pune

Abstract
Wireless Sensor Networks (WSNs) consist of spatially distributed sensor nodes that cooperate through wireless communication to collect and transmit information about physical environments. Knowledge of the geographic position of individual sensor nodes is fundamental to applications such as environmental monitoring, target tracking, geographical routing, disaster management, and Internet of Things (IoT) systems. However, equipping every sensor node with a Global Positioning System (GPS) receiver or transferring localization information to a centralized processing unit can increase hardware cost, communication overhead, computational complexity, and energy consumption. These challenges motivate the development of distributed localization techniques in which sensor nodes estimate their positions using locally available information.
This paper proposes a vertex-centric graph-theoretic localization framework in which a wireless sensor network is represented as a graph, with sensor nodes modeled as vertices and communication relationships represented by edges. Each node estimates its position using information obtained from its local neighborhood rather than depending on a centralized localization server. The proposed framework combines neighborhood connectivity, relative distance information, local geometric constraints, and iterative position refinement. The first objective is to develop a vertex-centric localization mechanism that enables individual nodes to estimate their positions from local neighborhood information. The second objective is to reduce energy consumption and communication overhead by shifting localization computations from a centralized processor to the sensor nodes themselves. The proposed approach is designed to provide a balance among localization accuracy, computational cost, communication overhead, and energy consumption. The paper presents the theoretical formulation, proposed algorithmic architecture, performance metrics, and experimental methodology for evaluating the framework against conventional centralized and distributed localization approaches.

Keywords: wireless sensor networks, node localization, graph theory, vertex-centric computing, distributed localization, energy efficiency, communication overhead, sensor networks

1. Introduction

Wireless Sensor Networks (WSNs) have become an important technological foundation for distributed sensing and monitoring applications. A WSN normally consists of a collection of sensor nodes equipped with sensing, processing, memory, and wireless communication capabilities. Since sensor nodes are

often deployed over large geographical regions, the physical position of a node is an important component of the information generated by the network. Sensor observations without corresponding spatial information may have limited usefulness in applications where the location of an event is required.

Localization refers to the process through which sensor nodes determine their geographic coordinates. Conventional approaches frequently employ GPS-enabled nodes, anchor nodes, distance measurements, angle measurements, received signal strength, or combinations of these techniques. However, providing every node with GPS or sophisticated positioning hardware is often unsuitable for resource-constrained WSNs. Previous research has consequently investigated localization based on network connectivity, ranging measurements, multil-ateration, graph constraints, and cooperation among neighbouring nodes (Doherty et al., 2001; Shang et al., 2003).

Graph theory provides a natural mathematical representation of a WSN. Let the sensor network be represented by a graph $(G = (V, E))$, where (V) represents sensor nodes and (E) represents wireless communication links. Two nodes are connected by an edge when they can communicate directly or satisfy a predefined neighborhood relationship. Under this representation, localization becomes a graph-based position estimation problem. Connectivity relationships can impose geometric constraints on possible node locations, while distance or relative-position information can provide additional constraints.

Doherty et al. (2001) demonstrated that connectivity relationships can be converted into geometric constraints for estimating sensor positions. Their formulation represented the sensor network as a graph whose vertices correspond to nodes and whose edges correspond to communication constraints. Similarly, Shang et al. (2003) proposed localization using connectivity information and multidimensional scaling, demonstrating that geographic positions can be estimated even when direct distance information is limited.

An important limitation of many localization approaches is the computational and communication cost associated with collecting network-wide information. A centralized system may require sensor nodes to transmit their connectivity or ranging information to a central processor. The central processor performs the localization computation and subsequently distributes position information back to the nodes. Although this approach can provide a global view of the network, repeated communication between the nodes and the central processor can consume significant energy.

The present study therefore focuses on a vertex-centric localization framework. In the proposed approach, each sensor node is treated as an independent computational vertex that uses information from its local neighbourhood to update its position estimate. Rather than requiring the entire network topology to be available at a central processor, the framework distributes the localization computation across sensor nodes.

The research therefore combines two important dimensions of WSN localization: local graph-based position estimation and energy-efficient distributed computation.

2. Background and Related Work

2.1 Localization in Wireless Sensor Networks

Localization is one of the fundamental problems in wireless sensor networks because many applications require sensor measurements to be associated with geographic coordinates. Localization approaches are commonly categorized as range-based and range-free methods.

Range-based techniques use physical measurements such as received signal strength, time of arrival, time difference of arrival, or angle of arrival to estimate distances or directions between nodes. Multil-ateration can then be applied to determine an unknown node's coordinates. Savvides et al. (2002) investigated collaborative multil-ateration in which sensor nodes use measurements from neighbouring nodes and known beacon positions to estimate their locations. Their work also considered a distributed approximation of the localization computation, demonstrating the feasibility of collaborative computation among resource-constrained sensor nodes.

Range-free approaches, in contrast, do not necessarily require accurate distance measurements. Connectivity information can be used to establish approximate geometric relationships among nodes. Shang et al. (2003) developed a connectivity-based localization approach using multidimensional scaling, showing the potential of estimating positions from network connectivity information.

Both approaches have advantages and limitations. Range-based localization can potentially provide higher accuracy but depends on measurement quality and may require additional hardware. Range-free methods generally reduce hardware requirements but may sacrifice positioning precision.

2.2 Graph-Theoretic Representation

Graph theory provides an effective mathematical model for WSN localization. Let

$$[G = (V, E)]$$

Represent a sensor network, where

$$[V = \{v/1, v/2, \ldots\ldots, vn\}]$$

is the set of sensor nodes

For every node (vi), its one-hop neighbour-hood is defined as

$$[Ni = \{vj\epsilon V : (vi, vj)\epsilon E\}]$$

The degree of node (vi) is

$$[di = |Ni|.]$$

The neighbour-hood therefore provides a local description of the network topology available to node (vi).

If the actual position of node (vi) is represented by

$$[pi = (xi, yi),]$$

Then localization seeks to determine an estimate

$$[pi = (\hat{x}\imath, \hat{y}\imath).]$$

Graph connectivity can provide constraints on the possible values of (pi). If two nodes are communicating within a radio range (R), then

If piandpjrepresent the positions of two communicating sensor nodes, and their radio communication range is R, then the connectivity constraint is:

$$\|p_i - p_j\| \leq R$$

where:

pi=(xi,yi) is the position of node i,

pj=(xj,yj) is the position of node j,

R is the maximum radio communication range.

Thus, for every pair of nodes connected by an edge (i,j) in the communication graph,

$$(xi - xj)^2 + (yi - yj)^2 \leq R^2$$

The combination of these constraints creates a local geometric localization problem.

Graph-based approaches have been investigated using connectivity constraints, rigid graphs, trilateration, and graph embedding, and distributed iterative procedures. Rai and Varma (2016), for example, investigated the use of rigid graph theory for wireless sensor localization and used graph rigidity to analyze whether sensor nodes can be uniquely localized.

3. Problem Statement

Consider a wireless sensor network consisting of (n) sensor nodes randomly or systematically distributed over a two-dimensional monitoring region.

The network is represented as

$$[G = (V, E).]$$

A subset of nodes may have known coordinates and can act as anchor nodes, while the remaining nodes are localization targets.

The conventional centralized localization problem can be expressed as:

$$\min_{\{pi\}i\epsilon V} \sum_{(i,j)\epsilon E} (\|pi - pj\| - dij)^2$$

Although this formulation can estimate positions using information from the entire network, it requires network-wide information to be collected and processed. For a resource-constrained WSN, this can introduce communication and computational costs.

The research problem addressed in this study is therefore:

The proposed solution addresses this problem by decomposing the global localization problem into a set of local node-level estimation problems.

4. Objectives of the Study

The research is based on the following objectives.

To develop a vertex-centric localization framework based on graph theory that enables each node to estimate its position using local neighborhood information.

To minimize energy consumption and communication overhead by implementing distributed, node-level computations instead of centralized processing.

These objectives imply that the proposed framework must simultaneously address three major requirements:

- localization accuracy;
- computational decentralization; and
- Communication and energy efficiency.

5. Proposed Vertex-Centric Localization Framework

5.1 Conceptual Architecture

The proposed framework consists of five major stages:

- Graph construction
- Local neighbourhood discovery
- Local position estimation
- Iterative position refinement

- Distributed convergence

Each sensor node performs these operations using its locally available information.
The overall architecture can be represented as:

$$V \rightarrow G = (V, E) \rightarrow N_i \rightarrow p\iota(0) \rightarrow \widehat{p\iota(k} + 1) \rightarrow p\iota$$

Unlike centralized localization, the proposed framework does not require every node to transmit complete network information to a central processor.

5.2 Graph Construction

During initialization, each sensor node discovers its neighbouring nodes using communication-range information.
For node (vi),

$$dij = \|pi - pj\|$$

Neighbour given by:

$$Ni = \{vi\epsilon V: \|pi - pj\| \leq Ri$$

where (Ri) represents the communication range of node (i).
An adjacency matrix can be defined as

$$[A = [a\{ij\}],]$$

where

$$aij = \begin{cases} 1 & if vi and vj are neighbours \\ 0 & otherwise \end{cases}$$

$$Ni = \{Vj: dij \leq R\}$$

$$aij = \begin{cases} 1 & dij \leq Ri \\ 0 & dij > Ri \end{cases}$$

$$aij = \begin{cases} 1 & \|pi - pj\| \leq Ri \\ 0 & \|pi - pj\| > Ri \end{cases}$$

Thus, $aij = 1$ indicates a communication link between sensors vi andvj, while $aij = 0$ indicates that no direct communication link exists.
The resulting graph captures the communication structure of the sensor network.

5.3 Local Information Collection

Each node obtains information only from its neighbouring nodes. Depending on the available hardware, this information may include:

- node identifier;
- estimated distance;
- received signal strength;
- neighbor coordinates;
- anchor information;
- relative direction;
- confidence value associated with the measurement.

The proposed framework is deliberately designed so that the complete network topology does not have to be transmitted to a central processing unit.

5.4 Local Position Estimation

Suppose node (i) has (k) localized neighbors.

Let the current estimated positions of these neighbors be

$$pj = (\widehat{xj}, \widehat{yi}), j\epsilon Ni$$

$$dij = \|\widehat{pi} - \widehat{pj}\|$$

This quantity can then be used in the local position-refinement optimization:

$$pi^{k+1} = \arg\min \sum \|\widehat{pi} - \widehat{pj}\|$$

6. Distributed Algorithm

The proposed vertex-centric algorithm can be described as follows.

Algorithm 1: Vertex-Centric Distributed Localization

Input: Sensor graph $(G = (V, E))$, communication range (R), anchor positions, distance measurements, convergence threshold (\epsilon).

Output: Estimated position (pi) for each localizable sensor node.

- Deploy sensor nodes over the monitoring region.
- Construct the communication graph $(G = (V, E))$.
- Each node discovers its one-hop neighbors.
- Anchor nodes initialize their known coordinates.
- Each non-anchor node initializes its position estimate.
- Each node collects local neighbor information.
- Each node constructs its local localization error function.
- Each node calculates a new position estimate.
- Each node transmits only the updated local position information to relevant neighbors.
- Nodes repeat the position-update process.





This algorithm eliminates the requirement for a central processor to maintain the complete localization state of the network.

7. Energy-Efficient Communication Strategy

The second objective of the research is to reduce energy consumption and communication overhead.

In a WSN, communication can represent a significant source of energy consumption. Consequently, reducing unnecessary transmissions is important for extending network lifetime.

The proposed framework follows four principles.

7.1 Local Communication

Nodes communicate primarily with one-hop neighbors rather than transmitting network-wide localization information.

8. Experimental Evaluation Methodology

The proposed framework should be evaluated using simulation before deployment on physical sensor nodes.

A simulation environment can be developed using MATLAB, Python, NS-3, or another WSN simulation platform.

The following parameters can be varied:

Parameter	Suggested experimental values
Number of nodes	50, 100, 200, 500
Deployment area	100 × 100 m to 500 × 500 m
Anchor percentage	5%, 10%, 15%, 20%
Communication range	Multiple values
Measurement noise	Low, medium, high
Node distribution	Random and grid

Parameter	Suggested experimental values
Maximum iterations	50–500
Convergence threshold	(10^{-2}) to (10^{-5})
Network density	Sparse, medium, dense

The proposed framework should be compared with suitable existing localization approaches.
Possible comparison methods include:

- centralized multil-ateration;
- DV-based positioning;
- connectivity-based localization;
- distributed multil-ateration;
- graph-rigidity-based localization;
- other contemporary distributed localization algorithms.

Distributed localization studies have demonstrated that local communication and cooperative processing can be used to localize portions of a sensor network without requiring a fully centralized computation. Bose et al. (2022), for example, developed a distributed localization scheme for sensor networks modeled using unit disk graphs and investigated conditions under which nodes can be localized through local graph structures.

9. Expected Advantages of the Proposed Framework

The proposed vertex-centric graph-based framework is expected to provide several advantages.
First, it reduces dependence on centralized processing. Each node performs a portion of the localization computation, thereby distributing the computational workload.
Second, local neighborhood information reduces the amount of network-wide information that must be communicated.
Third, graph representation provides a flexible mathematical structure for integrating connectivity, distance, neighborhood density, and local geometric information.
Fourth, the approach is potentially scalable because additional nodes contribute additional computational resources rather than necessarily increasing the workload of a single central processor.
Fifth, the framework can potentially operate in situations where complete network connectivity information is unavailable.
These advantages are aligned with previous research demonstrating the feasibility of distributed localization, local graph-based processing, and peer-to-peer localization mechanisms. Savvides et al. (2002) showed that resource-constrained sensor nodes can collectively solve localization problems using distributed approximations, while Khan and Nguang (2021) demonstrated a distributed approach based on local neighborhoods and peer-to-peer alignment.

10. Research Hypotheses

The proposed study can be evaluated using the following hypotheses.

- The proposed vertex-centric graph-based localization framework can estimate sensor-node positions with acceptable localization accuracy using local neighborhood information.

- The proposed distributed approach reduces localization-related communication overhead compared with centralized localization.
- The proposed framework reduces overall energy consumption by limiting network-wide localization communication.
- The localization accuracy of the proposed approach remains acceptable as network size increases.
- The proposed framework demonstrates improved scalability because localization computation is distributed among sensor nodes.

10. Discussion

The central contribution of this research is the integration of graph-theoretic modeling and vertex-centric computation for WSN localization. Existing localization methods demonstrate that connectivity and geometric information can provide useful constraints for estimating node positions. However, many formulations still involve global optimization, centralized processing, or substantial communication between network components.

A vertex-centric approach changes the computational perspective. Instead of asking a central processor to solve a single large localization problem.

This transformation is particularly relevant for large-scale WSNs. The global problem may become computationally expensive as (n) increases, whereas local computations depend primarily on neighborhood size.

However, localization accuracy may be affected by sparse connectivity, measurement noise, poor anchor placement, and error propagation. Distributed methods must therefore balance localization accuracy against the communication savings obtained through local computation.

Graph rigidity is particularly relevant to this issue. If the local graph does not contain sufficient geometric constraints, multiple position configurations may satisfy the available measurements. Consequently, the proposed framework should include a local confidence or reliability mechanism that identifies nodes with insufficient geometric information.

The proposed methodology should therefore not be evaluated solely on localization accuracy. A meaningful comparison must jointly consider localization error, percentage of localized nodes, energy consumption, communication overhead, convergence rate, and scalability.

10. Limitations

The proposed framework has several potential limitations.

- First, local localization may be unreliable when a node has too few neighbors.
- Second, measurement errors can propagate through iterative position updates.
- Third, sparse networks may not provide sufficient graph constraints for unique localization.
- Fourth, anchor-node placement can influence the quality of the resulting coordinate system.
- Fifth, distributed computation may require additional iterations before convergence.
- Sixth, if the network contains disconnected components, nodes in components without sufficient reference information may only obtain relative positions rather than absolute geographic coordinates.
- These limitations should be explicitly examined during simulation and experimental evaluation.

11. Future Scope

The proposed framework can be extended in several directions.

11.1 Three-Dimensional Localization

The two-dimensional position vectorfor applications involving buildings, underwater networks, drones, and industrial environments.

11.2 Machine Learning-Based Error Correction

Machine learning models can be incorporated to estimate measurement reliability and compensate for RSSI or ranging errors.

11.3 Dynamic Networks

The framework can be extended to mobile sensor networks in which nodes change position over time.

11.4 Fault-Tolerant Localization

Fault detection can be integrated so that unreliable or malicious neighbor information does not significantly affect localization.

11.5 Energy-Adaptive Localization

The localization frequency can be adapted according to remaining battery energy. Nodes with low energy can reduce localization updates while nodes with higher energy can perform additional computation.

11.6 Hybrid Graph Models

Future research can combine graph connectivity, RSSI, angle information, and relative-distance measurements into a weighted graph.

12. Conclusion

This research proposes a vertex-centric graph-theoretic framework for distributed localization in wireless sensor networks. The framework is motivated by two objectives: enabling individual sensor nodes to estimate their positions using local neighbourhood information and reducing energy consumption and communication overhead through distributed node-level computation.

The proposed approach models the WSN as a graph in which sensor nodes represent vertices and communication relationships represent edges. Each node constructs a local neighbourhood, obtains information from neighbouring nodes, formulates a local localization error function, and iteratively updates its estimated position. The resulting framework transforms localization from a predominantly centralized problem into a collection of cooperative local computations.

The theoretical formulation provides a basis for measuring localization accuracy through mean localization error, while communication and energy models provide quantitative measures for evaluating the second objective. The proposed experimental methodology should compare the framework with centralized and existing distributed localization techniques under different network sizes, node densities, anchor percentages, communication ranges, and measurement-noise conditions.

The significance of the proposed research lies in its attempt to jointly address localization accuracy, scalability, energy efficiency, and communication overhead. Previous studies have established the usefulness of graph constraints, connectivity information, multil-ateration, rigid graphs, and distributed localization. The proposed framework builds on these ideas by emphasizing a vertex-centric computational model in which localization intelligence is placed directly at the sensor-node level.

The ultimate validation of the framework should be based on simulation and, where possible, real sensor-node experiments. In particular, the research should demonstrate whether the reduction in

network-wide communication can be achieved without causing an unacceptable increase in localization error or convergence time.

References

1. Bose, K., Kundu, M. K., Adhikary, R., &Sau, B. (2022). Distributed localization of wireless sensor network using communication wheel. Information and Computation, 289, 104962. https://doi.org/10.1016/j.ic.2022.104962
2. Doherty, L., El Ghaoui, L., &Pister, K. S. J. (2001). Convex position estimation in wireless sensor networks. In Proceedings of IEEE INFOCOM 2001 (Vol. 3, pp. 1655–1663). IEEE. https://doi.org/10.1109/INFCOM.2001.916662
3. Khan, F., &Nguang, S. K. (2021). Distributed localization algorithm for wireless sensor networks using range lookup and subregion stitching. IET Wireless Sensor Systems. https://doi.org/10.1049/wss2.12020
4. Kumar, S., &Hegde, R. M. (2017). A review of localization and tracking algorithms in wireless sensor networks. arXiv.
5. Niculescu, D., &Nath, B. (2004). Error characteristics of ad hoc positioning systems (APS). In Proceedings of the Fifth ACM International Symposium on Mobile Ad Hoc Networking and Computing (pp. 20–30). ACM. https://doi.org/10.1145/989459.989463
6. Rai, S. B., & Varma, S. (2016). An algorithmic approach to wireless sensor networks localization using rigid graphs. Journal of Sensors, 2016, Article 3986321. https://doi.org/10.1155/2016/3986321
7. Savvides, A., Park, H., & Srivastava, M. B. (2002). The bits and flops of the n-hop multil-ateration primitive for node localization problems. In Proceedings of the 1st ACM International Workshop on Wireless Sensor Networks and Applications (pp. 112–121). ACM.
8. https://doi.org/10.1145/570738.570755
9. Shang, Y., Ruml, W., Zhang, Y., &Fromherz, M. P. J. (2003). Localization from mere connectivity. In Proceedings of the 4th ACM International Symposium on Mobile Ad Hoc Networking and Computing (pp. 201–212). ACM. https://doi.org/10.1145/778415.778439
10. Yaghoubi, F., Abbasfar, A.-A., &Maham, B. (2014). Energy-efficient RSSI-based localization for wireless sensor networks. IEEE Communications Letters, 18(6), 973–976. https://doi.org/10.1109/LCOMM.2014.2320939